

# Tapes and flashings available with ALTA®

ANCI, Inc. has working alliances with other companies in the US. Tapes and flashings are printed with partner company brand.

## SHEATHING TAPE (Red)



Product	Number	Size	Roll/Cs	Cs/Pallet	Rolls/Pallet	Pallets/TL	Rolls/TL
Sheathing 48mm	204024850	48mm x 50m	36	90	3240	26	19584
Sheathing 72mm	204027250	72mm x 50m	24	90	2160	26	13056

Tear resistant; Moisture resistant; UV resistant; wide range of temperatures; does not contain VOC, HFCC or CFC, does not allow mold growth

Product	Thickness mil - mm	Tension lb/in - N/25mm	Adhesion oz/in - N/25mm	Stretch	Adhesive	Material
Sheathing Tape	3 - 0.076	30 - 131	40 - 10.9	120	Acrylic	BOPP
Nova Flash	3 - 0.325	85.0 375.0	65 oz/ yd2 N/25mm 18.25	21	Butyl	PP

## NOVA FLASH

Product	Number	Size	Roll/Cs	Cs/Pallet	Rolls/Pallet	Pallets/TL	Rolls/TL
Nova Flash 4"	99446	100 x 22.86	8	48	384	46	17664
Nova Flash 6"	99447	152 x 22.86	8	48	384	32	12288
Nova Flash 9"	99448	228 x 22.86	4	48	192	32	6144
Nova Flash 12"	99441	304 x 22.86	4	48	192	32	6144



## CANTECH 505

Product	Number	Size	Roll/Cs	Cs/Pallet	Rolls/Pallet	Pallets/TL	Rolls/TL
Cantech Flash 4"	505021002286	100 x 22.86	12	24	288	68	19584
Cantech Flash 6"	505521522286	152 x 22.86	8	24	192	68	13056
Cantech Flash 9"	505902282286	228 x 22.86	4	24	96	68	6528
Cantech Flash 12"	505303042286	304 x 22.86	4	24	96	68	6528

This tape is made of a multi-layer, UV-protected polyethylene film coated with a permanent bonding adhesive. Provides maximum protection against penetration of water and moisture around windows and doors.

### PRINCIPAL CHARACTERISTICS

- Meets all requirements of AAMA 711-13, Type A, Level 2.
- High shear adhesive provides excellent initial adhesion to surfaces.
- Strong and durable holding power.
- No primer required (AAMA 711-13 Type A) when applied to suitable surfaces.
- The film is flexible and conforms well to surfaces.
- Seals around fasteners and nails.
- Resistant to water and humidity.
- Avoids air infiltration.
- Excellent resistance to UV rays.

### APPLICATIONS

- Waterproof flashing membrane used to seal openings around windows and doors.
- Recommended on aluminum, wood, wood siding, fiberglass and vinyl windows and doors.
- Recommended on most house wraps, OSB, exterior plaster, and fiberboard.
- All surfaces above must be dry and clean to ensure proper contact.

